
TECHNICAL DATA SHEET

HAINING DULETAI NEW MATERIAL CO., LTD.

High speed door fabric

Product model: DLT-5803

A vinyl-laminated polyester fabric for dock shelter panels and high-speed doors.



MATERIAL SPECIFICATIONS

Technology:	Laminated
Structure:	PVC coating+polyester woven base fabric+PVC coating
Base fabric:	1000D*1000D/30*30
Weight:	1050gsm
Thickness:	0.82mm
Width:	1.05-3.2m
Roll length:	50m/100m
Surface:	Glossy/Matte
Blockout:	Extra blockout layer available
Tensile Strength	4000/4000 N/5cm DIN53354
Tear Strength	600/500 N/5cm DIN53356
Adhesion	100 N/5cm DIN53357
Colour:	Customized
Temperature:	-20~+70(°C)
FR certification:	Customized B1, B2, M1, M2, NFPA701, DIN75200;
Surface:	Double side acrylic larquered, Tear-Resistant, Waterproof
Packing:	Paper tube+PE film+Craft paper
MOQ:	3000meters for customization/

Values and available configurations are reproduced from the current material specification. Where a table lists several configurations, agree the selected construction for the order.

Listed fire-test grades or optional treatments do not certify every supplied configuration or finished product. Any test report applies to its submitted sample and stated test conditions.