Privacy Curtain Film

Product model: PVC Film for Medical Curtain

Calendered single-layer PVC film for healthcare privacy curtain panels.



TDS-PRIVACY-CURTAIN-001 / REV 01 / 13 November 2026

MATERIAL SPECIFICATIONS	
Technology	Calendering
Structure	Single-layer PVC film
Thickness	0.4 mm / approx. 15.7 mil
Maximum width	3.2 m / approx. 126.0 in
Transparency	0-50%
Colour	Customised
Formulation reference	50-60 PHR, according to customer requirements
UV resistance	ASTM G154-06; value listed as 3.5*
Vicat softening point	75 °C
Packing	PE foam or kraft paper with clear or coloured film
Options to specify	REACH/RoHS; anti-UV; cold-resistant; antistatic; flame-retardant configurations

* UV value is reproduced as listed; the rating scale and exposure duration are not specified. PHR is a formulation reference, not a measured hardness value.

ASTM E84-2025 | Class A

Tested sample: blue PVC film, 0.4 mm, 540 g/m².

Flame Spread Index: 10 | Smoke-developed Index: 450

SGS report AJFTS26003771R01_EN | 5 June 2026

Class A interior wall and ceiling finish category. Results apply to the tested sample and mounting arrangement.

View report

Available configurations must be agreed for the supplied film. Test results for one sample do not establish performance for every colour, formulation or finished curtain.